

# TECHNICAL DATA SHEET

## Vanishing Oil WB6

### Description

A modern high quality, ultra high performance vanishing oil to give significant enhancements in tool-life, operator comfort, and surface finish.

**Vanishing Oil WB6** is a special product which gives truly exceptional performance is rapidly drying, gives a non-oily film, and performs as well as high performance mineral oil based products.

Our Vanishing Oils are suitable for blanking, forming, punching, and pressing of ferrous and non-ferrous metals, giving superior surface finish and tool-life. The specific grade required should be selected according to the application.

### Benefits

Vanishing Oil WB6	
➤	Low Odour
➤	Faster Drying
➤	Multi-metal
➤	Non Staining
➤	Non-oily residues

### Typical Physical Properties

	Vanishing Oil WB6
Appearance	Amber Liquid
Specific Gravity	~0.83 @ 20°C
EP Performance	Very High
Viscosity at 40°C	5cSt
Lubricity	High
Sulphur (active)	Nil
Usage Concentration	As supplied

### Application Method

Our Vanishing Oils can top-up all common vanishing without adverse effect, although the benefits of using a John Neale Ltd product will not then be fully appreciated.

The oil can be applied by brush, swab, roller, or automatic applicator.

Vanishing Oil WB6